






Nominal power	kW	11,6
Reduced power	kW	3,6
Nominal water useful power	kW	10
Reduced water useful power	kW	2,5
Nominal efficiency	%	91,5
Reduced efficiency	%	96
Heating volume (min-max)	m ³	86 - 278
Nominal CO at 13% O ₂	%	0,011
Reduced CO at 13% O ₂	%	0,034
Nominal dust content at 13% O ₂	mg/Nm ³	11
Boiler capacity (H ₂ O)	l	14
Hopper capacity	kg	24,5
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,80 - 2,50
Autonomy (min-max)	h	9,8 - 30,6
Ignition electrical absorption (max)	W	420
Operating electrical absorption (max)	W	120
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	10
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	50
Mass of smoke (min-max)	g/sec	3,6 - 11
Exhaust fumes temperature (max)	°C	140
Net weight	kg	144
Gross weight	kg	154
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-



Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7014023	NEUTRAL STRUCTURE	EAN 8033123615013
6914003	White steel	EAN 8033123614788
6914002	Red steel	EAN 8033123614771
6914004	Silver steel	EAN 8033123614795

PLUS



Connection to the heating system



Hydraulic kit included



Cast iron burning pot



Overheating protection



Wi-Fi kit (optional)



Daily weekly programming



Connection to the external thermostat



Air temperature sensor




Water temperature sensor



Back exhaust


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	131,8	70


VOLUME (m ³)
0,74

LINING PACKING




	L (cm)	H (cm)	P (cm)
steel	59,1	12,5	109,2

STOCKING



TRANSPORT



57 pcs