




PRINCE³ PLUS

PELLET AIR PLUS - Pellet stoves



Nominal power	kW	10,5
Reduced power	kW	2,8
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	87,1
Reduced efficiency	%	93
Heating volume (min-max)	m ³	67 - 252
Nominal CO at 13% O ₂	%	0,007
Reduced CO at 13% O ₂	%	0,03
Nominal dust content at 13% O ₂	mg/Nm ³	12
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	22
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,6 - 2,4
Autonomy (min-max)	h	9,2 - 36,7
Ignition electrical absorption (max)	W	352
Operating electrical absorption (max)	W	77
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	3,1 - 6,5
Exhaust fumes temperature (max)	°C	228
Net weight	kg	105
Gross weight	kg	115
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	C



Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



A+

PLUS



Cast iron door



Overheating protection



Wi-Fi kit (optional)



Connection to the external thermostat



Sealed chamber



Duction with 1 independent motor



Remote control



Upper and back exhaust



Cast iron burning pot



Comfort mode




Daily weekly programming

MATCH

7015050	NEUTRAL STRUCTURE	EAN 8033123616867
6915030	Anthracite steel	EAN 8033123616430
6915031	White steel	EAN 8033123616447
6914043	Light bronze steel	EAN 8033123615884
6915032	Red steel	EAN 8033123616454
6915033	Silver steel	EAN 8033123616461


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	124,5	70


VOLUME (m ³)	0,70
--------------------------	------

LINING PACKING




	L (cm)	H (cm)	P (cm)
steel	57	11,5	104,7

STOCKING



TRANSPORT



57 pcs