






Nominal power	kW	8,5
Reduced power	kW	2,3
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	88,9
Reduced efficiency	%	92,2
Heating volume (min-max)	m ³	55 - 206
Nominal CO at 13% O ₂	%	0,014
Reduced CO at 13% O ₂	%	0,032
Nominal dust content at 13% O ₂	mg/Nm ³	29,4
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	15
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,52 - 1,98
Autonomy (min-max)	h	7,6 - 28,8
Ignition electrical absorption (max)	W	346
Operating electrical absorption (max)	W	47
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11,6
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	2,22 - 4,72
Exhaust fumes temperature (max)	°C	208,8
Net weight	kg	70 - 88
Gross weight	kg	80 - 98
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-



Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



A+

PLUS



Sealed chamber



Cast iron burning pot



Overheating protection



Comfort mode



Wi-Fi kit (optional)



Remote control



Daily weekly programming



Connection to the external thermostat




Back exhaust

MATCH

7017030		Anthracite steel	EAN 8033123618298
7017031		White steel	EAN 8033123618304
7017028		Red steel	EAN 8033123618427
7017029		Silver steel	EAN 8033123618434
7016056		Natural Acrylic Stone Alpine White	EAN 8033123617796
7016057		Natural Acrylic Stone Grey	EAN 8033123617802


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	124,5	70


VOLUME (m ³)
0,70

LINING PACKING



L (cm)	H (cm)	P (cm)
-	-	-

STOCKING



TRANSPORT

